
multicomp




Specifications

Nominal Capacity	: 50mAh (470h)
	(Continuously discharged under 30kΩ load till 2.0V end-point voltage at the temperature of 23°C ±3°C)
Nominal Voltage	: 3V
Off-Load Voltage	: 3.2V ~ 3.6V
Self-Discharge Rate per Year	: ≤3%
Max. Pulse Current	: 5mA
Max. Continuous Discharge Current	: 2mA
Standard Current	: 0.1mA
Battery Terminals	: Pressure Contact
Operating Temperature	: -20°C to 60°C
Dimensions (Dia. × Height)	: 12.5mm × 2.5mm
Weight	: 0.9g


Discharge on different load (23°C)







Product Configuration



Notes

The max pulse current means that when a 40% discharged battery is discharged in this current for 15 seconds; the loaded voltage should be higher than 2.0V at 23°C.

The maximum continuous discharge current means that when the battery is discharged in this current to 2.0V at 23°C, 50% of nominal capacity could be obtained.

Part Number Table

Description	Part Number
Lithium Manganese Dioxide Button Cell, CR1225, 3V	MC002789

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com

